



Angle bar

Assortment: 20x20mm to 160x160mm; 4m to 12m long
Grades: S235JR, S275JR, S355JR & S355JO
Standards: EN 10056-2:1993, BS-EN 10025-2004




Square bar

Assortment: 8x8mm to 80x80mm; 4m to 12m long
Grades: S235JR, S275JR, S355JR & S355JO
Standards: EN 10059:2004; BS-EN 10025-2004




Square profiles

Thickness: 0.60mm – 16mm; Size: 10x10 – 300x300mm;
Length: 4m to 15m
Grades: S235JR, S275JR, S355JR & S355JO
Standards: BS EN 39: 2001, 6323, 6363, EN10219-2, EN 10305




Steel beams

Assortment: RSJ, IPE, UB, UC, IPN, HEA, HEB
Grades: S275JR, S355JO
Standards: BS 4-1:2005, EN 10024:2005, EN 10034:1993, DIN 100




Flat bar

Assortment: 10x3mm to 300x30mm; 4m to 12m long
Grades: S235JR, S275JR, S355JR & S355JO
Standards: EN 10058:2004; BS-EN 10025-2004




Round bar

Assortment: 6mm to 80mm; 4m to 12m long
Grades: S235JR, S275JR, S355JR & S355JO
Standards: EN 10060:2004; BS-EN 10025-2004




Rectangular profiles

Thickness: 0.60mm – 16mm; Size: 20x10mm – 300x200mm;
Length: 4m to 15m
Grades: S235JR, S275JR, S355JR & S355JO
Standards: BS EN 39: 2001, 6323, 6363, EN10219-2, EN 10305




Steel channels

Assortment: PFC, UPE, UPN; Length 6-12m
Grades: S355JO, S275JR
Standards: BS 4-1:2005, EN 10279:2000, DIN 10026




Rebar in coil

Assortment: 5.5mm to 26mm; min;
Weight: 1900 - max. 3200 kgs;
Height: 1400 - 1850mm, Grades: B500B, B500C
Standards: BS 4449:2005, CARES Certified




Galvanized coils and sheets

Thickness: 0.2mm – 3mm; Width: MAX. 1500mm;
Grades: DX51D + Z / DX52D + Z / DX53D + Z / DX54D +
Standards: EN 10346



Circular profiles

Thickness: 0.60mm – 16mm;
Size: Ø13mm – Ø273mm; Length: 4 to 15 meters
Grades: S235JR, S275JR, S355JR & S355JO
Standards: BS EN 39: 2001, 6323, 6363, EN10219-2, EN 10305




Hot rolled sheet / coils

Thickness: 1.2mm – 25mm; Width: MAX. 2000mm;
Weight: 10-39mt; Grades: S235JR- JO, J2, J2H, + N, + M / S275JR- JO, J2, J2H, + N, + M / S355JR- JO, J2, J2H, + N, + M
Standards: EN 10025-2




Reinforcing bar

Assortment: 6mm to 40mm; 6m to 18m long
Grades: B500B, B500C, B420B, B460B, S420 & Gr250
Standards: BS 4449:2005, BS 4482:2005, CARES Certified




Steel billets

Assortment: 100x100mm to 150x150mm; 6m to 12m long
Grade: ST3KP/ST3SP/ST3PS/ST4KP/ST4PS/ST4SP, B500B, B500C
Standard: GOST 380-2005, BS4449:2005, EN10080:2010



Hot rolled sheets / plates

Thickness: 1.2mm – 100mm; Width: MAX. 3000 mm
Grades: S235JR- JO, J2, J2H, + N, + M / S275JR- JO, J2, J2H, + N, + M / S355JR- JO, J2, J2H, + N, + M
Standards: BS EN 10025-2 : 2004, BS EN 10111 : 2008



Wire rod and wire mesh

Assortment: 5.5-26mm, min. 1900 - max. 3200 kg
Grades: SAE1008, SAE101, SAE1012, SAE1015
Standards: DIN EN 10017, DIN EN 1010